

 EVNISKO

EVNISKO HOME3

עמדת טעינה פרטית חד/תלת-פאזית 22kW_ט TYPE2

מפרט טכני



שירות
ואחריות
NISKO



שליטה
באפליקציה
BLUETOOTH



התקן
זליגה
מובנה DC



טל.ח | התמונות להמחשה בלבד

 
IP66 IK08



2Years
GUARANTEE

***2650**

EVNISKO שירות מוקד EVNISKOHOME



קבוצת ניסקו בע"מ
המע"ן 41 מודיעין
www.evnisko.com
www.niskoelec.com

NISKO
GROUP

EVNISO HOME3

מפרט טכני

POWER INPUT

AC EV charger

INPUT VOLTAGE	3 phase 3x400VAC 50/60Hz
INPUT CURRENT	3 phase 3x32A

POWER OUTPUT

OUTPUT POWER	22 kW
OUTPUT TYPE	Type2 Cable (Mode 3)
CABLE LENGTH	5 meters
TYPE OF CABLES	STRAIGHT TPU
SIMULTANEOUS CHARGING	1

USER INTERFACE AND CONTROL

USER INTERFACE	LED status indicator
	PLUG & CHARGE
ACCESS CONTROL	RFID (Mifare ISO & IEC 14443A)
	MOBILE App (Default)

CONNECTIVITY

COMMUNICATION INTERFACE	BLUETOOTH
	RFID IEC 1444 3A

CERTIFICATE

VERSION	EN/IEC 61851-1:2019, EN/IEC 61851-21-2:2018, IEC 62955:2018
---------	---

SAFETY PROTECTIONS

OVER CURRENT PROTECTION, RESIDUAL CURRENT PROTECTION, GROUND PROTECTION, OVER/UNDER VOLTAGE PROTECTION, SURGE PROTECTION, OVER/UNDER TEMPERATURE PROTECTION

PHYSICAL

MOUNTING METHOD	WALL-mounted
	POLE-mounted
ENCLOSURE	Plastic
DIMENSIONS (LxWxH)	PRODUCT 255x100x324mm
	PACK 460x280x220mm
WEIGHT	NET 5.8Kg
	GROSS 6.5Kg

ENVIRONMENTAL

OPERATING TEMPERATURE	-30°C to +55°C
INSTALLATION	INDOOR / OUTDOOR
HUMIDITY	MAX.95% (non-regulating)

STANDARDS

CONFORMITY	IEC 61851-1
DEGREE OF PROTECTION	IP66
IMPACT STRENGTH	IK08
RESIDUAL CURRENT DETECTION (RCD)	BUILT IN 30mA AC TypeA + 6mA DC
STANDBY POWER	<3W
MEASURING ACCURACY	1%
COOLING	Natural cooling
WARRANTY	2 YEARS