



תאורת הצפה SMD דק, עם עיצוב חדשני כולל זרוע מתכונת של 270 מעלות. כיסוי פרוסט מונע סנוור. לגוף יעילות אורית גבוהה - 90lm/W. מהווה תחליף אידיאלי לכל פנסי הצפה הקיימים בשוק כיום - נל"ג, קוורץ, מטלהלייד וכספית ולכלל סוגי ההספקים הקיימים. חיסכון אנרגטי של עד 70% בהשוואה למטלהלייד! משמע, החזר השקעה מהיר. ייעודי להתקנה חיצונית, בבתים, גינות, שטחים פתוחים, מפעלים ועוד.

מק"ט - 17820184

דגם - E027E1

קישור לדף מוצר ואביזרים נלווים באתר



**2Years**  
Guarantee

220-240V  
50-60Hz



IP65

### DIMENSIONS & WEIGHT

### מידות ומשקל

Length	211mm
Width	34mm
Height	177mm
Product weight	470g

### MATERIALS & COLORS

### מבנה וגימור

Product color	white
Body material	Plastic
Cover finishing	Frosted
Cover material	Plastic

## ELECTRICAL DATA

## נתונים חשמליים

Nominal wattage	30W
Nominal current	0.14A
Nominal voltage	220-240V
Mains frequency	50/60Hz
Protection class	Class 1
Operating mode	Internal LED driver
Driver manufacturer	Integrated
Power factor	>0.95
THDi	<19%

## APPLICATION & MOUNTING

## יישומים

Application environment	OUTDOOR
Mounting type	Surface Pole
Mounting location	Ceiling/Wall-mounted Pole
Type of protection	IP65

## CERTIFICATES & STANDARDS

## תקנים

Nisko Class	ECO 2 Years
CE	IEC 60598-1 IEC 60598-2-5
EMC	IEC 55015 IEC 61000-3-2 IEC 61000-3-3 IEC 61547
IP 60529	IP65

## PHOTOMETRIC DATA

## אופטיקה

Luminous efficacy	90Lm/W
Luminous flux	2700Lm
CCT	3000K
CRI	>80
LED manufacturer	XuYu
Chip type	SMD 2835
Beam angle	120°
Efficiency	100%